



2 TUBI (1 batteria)
2 PIPE (1 coil)



TAGLIA - SIZE		FX 130	FX 230	FX 330	FX 430	FX 530	FX 630	FX 730	FX 830	FX 930	FX 1030	FX 1130	FX 1230
Potenzialità frigorifera	Totale - Total	W	1.500	2.000	2.530	3.020	3.750	4.250	5.520	6.420	7.530	9.020	10.710
Cooling capacity	Sensibile - Sensible	W	1.290	1.620	2.070	2.380	3.080	3.440	4.600	5.200	6.430	7.300	8.740
Potenzialità Termica - Heating capacity		W	3.430	4.330	5.510	6.140	7.980	9.210	12.160	13.620	17.020	19.070	24.200
Portata aria - Air flow		m ³ /h	350	360	435	447	647	665	975	1.003	1.431	1.472	1.908
Livello sonoro - Sound level	(Min-Med-Max)	dB(A)	28-34-38	28-34-38	29-35-40	29-35-40	30-36-42	30-36-42	32-38-43	32-38-43	37-44-49	37-44-49	38-45-50

Versione incasso verticale con falso telaio e pannello di copertura (per installazione su nicchia nel muro) Vertical concealed version with false frame and covering panel (for wall niche installation)													
Modello Model		FX-PV 130	FX-PV 230	FX-PV 330	FX-PV 430	FX-PV 530	FX-PV 630	FX-PV 730	FX-PV 830	FX-PV 930	FX-PV 1030	FX-PV 1130	FX-PV 1230
Codice - Code		01013014	01023014	01033014	01043014	01053014	01063014	01073014	01083014	01093014	01103014	01113014	01123014
L1	mm	650	650	850	850	1.050	1.050	1.250	1.250	1.450	1.450	1.650	1.650
H1	mm	620	620	620	620	620	620	620	620	620	620	620	620
S1	mm	235	235	235	235	235	235	235	235	235	235	235	235
LP	mm	700	700	900	900	1.100	1.100	1.300	1.300	1.500	1.500	1.700	1.700
HP	mm	670	670	670	670	670	670	670	670	670	670	670	670
Peso netto - Net weight		kg	24,0	24,5	29,6	30,4	38,5	39,5	45,2	46,7	52,5	54,0	62,8
Composizione dell'unità Unit's components		FX-CB Ventilconvettore ad incasso verticale (versione "CB") - Vertical concealed fan-coil ("CB" version) FTZ Falso telaio in lamiera zincata - False frame made of galvanized steel R90M-C Plenum a 90° di mandata aria Coibentato - Insulated Air supply 90° plenum MRS 1 Morsetteria tipo "Mamut" (comando remoto escluso) - "Mammoth" type terminal board (Remote control not included) PNA Pannello in lamiera preverniciata bianca (simile a RAL 9010) - Panel made of white (similar to RAL 9010) pre-painted steel											

Versione incasso orizzontale con pannello di copertura (per installazione su controsoffitto) Horizontal concealed version with covering panel (for false ceiling installation)													
Modello Model		FX-PH 130	FX-PH 230	FX-PH 330	FX-PH 430	FX-PH 530	FX-PH 630	FX-PH 730	FX-PH 830	FX-PH 930	FX-PH 1030	FX-PH 1130	FX-PH 1230
Codice - Code		01013015	01023015	01033015	01043015	01053015	01063015	01073015	01083015	01093015	01103015	01113015	01123015
L2	mm	545	545	745	745	945	945	1.145	1.145	1.345	1.345	1.545	1.545
H2	mm	590	590	590	590	590	590	590	590	590	590	590	590
S2	mm	215	215	215	215	215	215	215	215	215	215	215	215
LP	mm	700	700	900	900	1.100	1.100	1.300	1.300	1.500	1.500	1.700	1.700
HP	mm	670	670	670	670	670	670	670	670	670	670	670	670
Peso netto - Net weight		kg	16,9	17,4	21,0	21,8	28,4	29,4	33,6	35,1	39,3	40,8	48,1
Composizione dell'unità Unit's components		FX-CK Ventilconvettore ad incasso orizzontale (versione "CK") - Horizontal concealed fan-coil ("CK" version) R90M-C Plenum a 90° di mandata aria Coibentato - Insulated Air supply 90° plenum MRS 1 Morsetteria tipo "Mamut" (comando remoto escluso) - "Mammoth" type terminal board (Remote control not included) PNA Pannello in lamiera preverniciata bianca (simile a RAL 9010) - Panel made of white (similar to RAL 9010) pre-painted steel											

Accessori raccomandati: Comando remoto (vedi sezione CR-ICD-HTR-HTN)

Recommended accessories: Remote control (see CR-ICD-HTR-HTN section)